

# ANCHORAGE CONNECTOR SPECIFICATIONS



Find the right anchorage connector that meets all of your work and rescue specifications.

## ANCHORS

	SKU	Weight	MBS	Material	Certifications
1/2" Removable Anchor	HD26233	3.2 oz (91 g)	12 kN (2700 lbf)	Zinc Plated Steel and Copper, Aluminum Alloy and Stainless Steel	USA Made
1" Fall Protection RB Anchor	HD26224	1.00 lbs (454 g)	44 kN (10000 lbf)	Zinc Plated Steel and Copper, Aluminum Alloy and Stainless Steel	EN 795   CE   ANSI Z359.1 (2007)   USA Made
3/4" Fall Protection RB Anchor	HD26223	8.0 oz (227 g)	22 kN (5000 lbf)	Zinc Plated Steel and Copper, Aluminum Alloy and Stainless Steel	EN 795   CE   ANSI Z359.1 (2007)   USA Made
3/4" Toggle Lok Anchor	HD26225	8.0 oz (227 g)	22 kN (5000 lbf)	Zinc Plated Steel and Copper, Aluminum Alloy and Stainless Steel	EN 795   CE   ANSI Z359.1 (2007)   USA Made
Climb Tech I Beamer Clamp	HD26229	3.40 lbs (1.54 kg)	22 kN (5000 lbf)	Aluminum Alloy, Aluminum Bronze and Stainless Steel	EN 795   CE   ANSI Z359.1 (2007)
Fallstop Man-Rated Drum Winch: 100 ft	HD26098	34.00 lbs (15.42 kg)			
Mega Swivel 10K Concrete	HD26227	1.80 lbs (816 g)	44 kN (10000 lbf) WLL: 5000 lbf	Zinc Plated Steel	EN 795   CE   ANSI Z359.1 (2007)   USA Made
Mega Swivel 10K Steel	HD26226	2.00 lbs (907 g)	44 kN (10000 lbf) WLL: 5000 lbf	Zinc Plated Steel	EN 795   CE   ANSI Z359.1 (2007)   USA Made
PMI/SMC Spec Hook	HD26220 HD26222	10.2 oz (289 g)	Saddle: 35 kN (8000 lbf) Tip: 12 kN (3000 lbf)	Aluminum	USA Made
SMC Rescue StayK	SM305100	9.24 lbs (4.19 g)	Dependent on ground placement, density and composition		USA Made
Tractel Beam Clamp	HD26067	12.32 lbs (5.6 kg)	24 kN (5400 lbf)		CSA   ANSI Z359.1 (2007)

## RIGGING HARDWARE

	SKU	Weight	MBS	Material	Certifications
SMC Descending Ring	SM81600	0.4 oz (11 g)	15 kN (3372 lbf)	Aluminum	USA Made
SMC Mini Rigging Plate	SM130301N SM130302N	2.8 oz (79 g)	36 kN (8093 lbf)	Aluminum	NFPA 1983 (2012), G   Berry Compliant   USA Made
SMC NFPA Rigging Plate	SM130005	11.4 oz (323 g)	50 kN (11240 lbf)	Anodized Aluminum	NFPA 1983 (2012), G   Berry Compliant   USA Made
Steel O Ring	HD26049	9 oz (256 g)	44 kN (10000 lbf)	Steel	
SMC Rescue Swivel	SM136000N SM136007N	4.5 oz (128 g)	44 kN (10000 lbf)	Anodized Aluminum	NFPA 1983 (2012), G   Berry Compliant   USA Made
SMC Rigging Ring	SM81503 SM81505	0.9 oz (26 g)	32 kN (7194 lbf)	Aluminum	USA Made

## PORTABLE ANCHORS

	SKU	Weight	Max Height	Configuration Options	Certifications
Sked® Evac Tripod	SK700	71.0 lbs (32.2 kg)	10 ft	Tripod	EN 795   CE   USA Made
TerrAdaptor™ Multi Pod	SM230100N		10 ft	Monopod, Bipod, Tripod or Quadpod	NFPA 1983 (2012), G   USA Made

continued on next page

Pigeon Mountain Industries, Inc. | PO Box 803, LaFayette, GA 30278 | Fax: 706-764-1531 | Email: custserv@pmirope.com

## ANCHOR/RIGGING STRAPS

	SKU	Weight	Length	MBS	Certifications
ClimbTech Drop Through Anchor Kit	HD26232	2.60 lbs (1.179 kg)	8.50 ft (2.6 m)	22 kN (5000 lbf)	EN 795   CE   ANSI Z359.1 (2007)   USA Made
ClimbTech Wire Rope Choker Sling 3ft	HD26238	1.10 lbs (499 g)	3 ft (91.4 cm)	22 kN (5000 lbf)	ANSI Z359.1 (2007)   USA Made
ClimbTech Wire Rope Choker Sling 6ft	HD26239	1.60 lbs (730 g)	6 ft (182.9 cm)	22 kN (5000 lbf)	ANSI Z359.1 (2007)   USA Made
ClimbTech Wire Rope Sling 3ft	HD26236	1.00 lbs (453 g)	3 ft (91.4 cm)	22 kN (5000 lbf)	ANSI Z359.1 (2007)   USA Made
ClimbTech Wire Rope Sling 6ft	HD26237	1.45 lbs (657 g)	6 ft (182.9 cm)	22 kN (5000 lbf)	ANSI Z359.1 (2007)   USA Made
heightec® Steel Anchor Sling	HD26166	1.69 lbs (771 g)	6.56 ft (2 m)	30 kN (6744 lbf)	EN 354, EN 795-B
PMI® Anchor Sling 3ft	SG51029	11 oz (311 g)	3 ft (91.4 cm)	Basket (U): 49.2 kN (11060.60 lbf) End-to-End: 28.7 kN (6452.02 lbf) Choker: 22.6 kN (5080.69 lbf)	NFPA 1983 (2012), G   ANSI Z359.1 (2007)   USA Made
PMI® Anchor Sling 4ft	SG51030	12 oz (354 g)	4 ft (121.9 cm)	Basket (U): 49.2 kN (11060.60 lbf) End-to-End: 28.7 kN (6452.02 lbf) Choker: 22.6 kN (5080.69 lbf)	NFPA 1983 (2012), G   ANSI Z359.1 (2007)   USA Made
PMI® Anchor Sling 6ft	SG51031	14 oz (410 g)	6 ft (182.9 cm)	Basket (U): 49.2 kN (11060.60 lbf) End-to-End: 28.7 kN (6452.02 lbf) Choker: 22.6 kN (5080.69 lbf)	NFPA 1983 (2012), G   ANSI Z359.1 (2007)   USA Made
PMI® Choker Sling 3 ft	SG51213	15.20 oz (431 g)	3 ft (91.4 cm)	Basket (U): 48.7 kN (10948.20 lbf) End-to-End: 22.2 kN (4990.75 lbf) Choker: 20.8 kN (4676.03 lbf)	NFPA 1983 (2012), G   ANSI Z359.1 (2007)   USA Made
PMI® Choker Sling 4 ft	SG51242	1.05 lbs (476 g)	4 ft (121.9 cm)	Basket (U): 48.7 kN (10948.20 lbf) End-to-End: 22.2 kN (4990.75 lbf) Choker: 20.8 kN (4676.03 lbf)	NFPA 1983 (2012), G   ANSI Z359.1 (2007)   USA Made
PMI® Choker Sling 6 ft	SG51214	1.20 lbs (544 g)	6 ft (182.88 cm)	Basket (U): 48.7 kN (10948.20 lbf) End-to-End: 22.2 kN (4990.75 lbf) Choker: 20.8 kN (4676.03 lbf)	NFPA 1983 (2012), G   ANSI Z359.1 (2007)   USA Made
PMI® Choker Sling 8 ft	SG51243	1.35 lbs (612 g)	8 ft (243.84 cm)	Basket (U): 48.7 kN (10948.20 lbf) End-to-End: 22.2 kN (4990.75 lbf) Choker: 20.8 kN (4676.03 lbf)	NFPA 1983 (2012), G   ANSI Z359.1 (2007)   USA Made
PMI® Vari-Rigger	SG51033	1.50 lbs (680 g)	Adjustable: 2 ft (60.96 cm) - 8 ft (243.84 cm)	22 kN (5000 lbf)	USA Made
Skedco Anchor Sling 7 ft	SK910	1 lbs (454 g)	7 ft (213.36 cm)	71 kN (16000 lbf)	USA Made
Skedco Anchor Sling 8 ft	SK9118	2 lbs (907 g)	8 ft (243.84 cm)	86 kN (19334 lbf)	USA Made
Skedco Anchor Sling 12 ft	SK91112	2.375 lbs (1.089 kg)	12 ft (365.76 cm)	86 kN (19334 lbf)	USA Made
Skedco Anchor Sling 20 ft	SK91120	2.625 lbs (1.179 kg)	20 ft (609.60 cm)	86 kN (19334 lbf)	USA Made