

Find the right braking device that meets all of your work and rescue specifications.

FIGURE 8'S

	SKU	Weight	Length	Width	Thickness	Material	Finish	Max Rope Size	Breaking Strength	Certifications
SMC/RA Rescue 8 (w/o Ears)	SM128701N SM128702N	6.5 oz (184 g)	6.00" (15.6 cm)	5.25" (13.3 cm)	0.50" (1.3 cm)	Aluminum	Anodized Hard Coat	13 mm	32 kN (7194 lbf)	NFPA 1983 (2012), G (for ropes 11 mm - 16 mm) NFPA 1983 (2012), T (for ropes 9.5 mm - 12.5 mm) Berry Compliant USA Made
SMC/RA Rescue 8 (w/o Ears)	SM129000	5.3 oz (150 g)	6.16" (15.2 cm)	3.40" (8.6 cm)	0.50" (1.3 cm)	Aluminum	Anodized Hard Coat	13 mm	32 kN (7194 lbf)	Berry Compliant USA Made
SMC/RA Large Figure 8	SM142000	8.0 oz (227 g)	7.15" (18.2 cm)	6.40" (16.3 cm)	0.50" (1.3 cm)	Aluminum	Anodized Hard Coat	16 mm	32 kN (7194 lbf)	Berry Compliant USA Made
PMI Large Steel Figure 8	HD26100	1.50 lbs (680 g)	6.75" (17.1 cm)	6.75" (17.1 cm)	0.50" (1.3 cm)	Steel	Natural	16 mm	28 kN (6295 lbf)	Berry Compliant USA Made
SMC Mountaineering 8	SM81700 SM81702	2.8 oz (79 g)	4.62" (11.7 cm)	2.96" (7.5 cm)	0.38" (9.0 mm)	Aluminum	Anodized Hard Coat	12.5 mm	27 kN (6070 lbf)	Berry Compliant USA Made
SMC Descent Control 8	SM113000	7.5 oz (213 g)	5.18" (13.2 cm)	3.61" (9.2 cm)	0.38" (9.0 mm)	Stainless Steel	Polished	13 mm	89 kN (20,000 lbf)	Berry Compliant USA Made
SMC Escape 8	SM126501N SM126502N	1.7 oz (48 g)	2.80" (7.1 cm)	2.73" (6.9 cm)	0.38" (9.0 mm)	Aluminum	Anodized	13 mm	14 kN (3147 lbf)	NFPA 1983 (2012), E (for ropes 7.5 mm - 9.5 mm) Berry Compliant USA Made
PMI PED	HD26024	1.5 oz (42 g)	2.94" (7.5 cm)	1.63" (4.1 cm)	0.50" (1.3 cm)	Aluminum		9 mm	13.5 kN (3035 lbf)	Berry Compliant USA Made

BRAKE RACK ASSEMBLIES

	SKU	Weight	Length	Width	Thickness	Frame Material	Bar Material	# of Bars	Certifications
SMC NFPA Rack Assembly Straight Eye	SM14001N	1.83 lbs (828 g)	14.40" (36.6 cm)	3.75" (9.5 cm)	1.00" (2.5 cm)	Stainless Steel	Stainless Steel & Anodized Aluminum	6	NFPA 1983 (2012), G (for ropes 11 mm - 16 mm) NFPA 1983 (2012), T (for ropes 9.5 mm - 12.5 mm) Berry Compliant USA Made
SMC NFPA Rack Assembly Long Rack	SM14003N	2.06 lbs (933 g)	17.90" (45.5 cm)	3.75" (9.5 cm)	1.00" (2.5 cm)	Stainless Steel	Stainless Steel & Anodized Aluminum	6	NFPA 1983 (2012), G (for ropes 11 mm - 16 mm) NFPA 1983 (2012), T (for ropes 9.5 mm - 12.5 mm) Berry Compliant USA Made
SMC NFPA U Rack	SM14600N	1.86 lbs (842 g)	14.00" (35.6 cm)	3.60" (9.1 cm)	1.00" (2.5 cm)	Stainless Steel	Stainless Steel & Anodized Aluminum		NFPA 1983 (2012), G (for ropes 11 mm - 16 mm) NFPA 1983 (2012), T (for ropes 9.5 mm - 12.5 mm) Berry Compliant USA Made
SMC NFPA Compact U Rack	SM14400N	1.66 lbs (754 g)	9.60" (24.4 cm)	3.60" (9.1 cm)	1.00" (2.5 cm)	Stainless Steel	Stainless Steel	4	NFPA 1983 (2012), G (for ropes 11 mm - 16 mm) NFPA 1983 (2012), T (for ropes 9.5 mm - 12.5 mm) USA Made
SMC NFPA Rack Assembly 90° Eye	SM14002N	1.83 lbs (828 g)	14.40" (36.6 cm)	3.75" (9.5 cm)	1.00" (2.5 cm)	Stainless Steel	Stainless Steel & Anodized Aluminum	6	NFPA 1983 (2012), G (for ropes 11 mm - 16 mm) NFPA 1983 (2012), T (for ropes 9.5 mm - 12.5 mm) Berry Compliant USA Made
SMC Micro U Rack	SM13700	14.1 oz (400 g)	8.50" (21.6 cm)	2.75" (7.0 cm)	0.78" (2.0 cm)	Stainless Steel	Stainless Steel	4	Berry Compliant USA Made

DEVICES

	SKU	Weight	MBS	Material	Rope Size	Certifications
heightec® Quadra™	HD26175	1.50 lbs (680 g)		Stainless Steel	10.5 mm - 11 mm	prEN 12841-A,B,C
heightec® Prism™	HD26181	1.13 lbs (500 g)		Stainless Steel Anodized Aluminum	10.5 mm - 11.5 mm	EN 341-B, EN 12841-C
SMC Spider	SM220300N	1.24 lbs (562 g)	13 kN (3174 lbf)		11 mm to 12.5 mm	NFPA 1983 (2012), T USA Made
Alpine Brake Tube	HD26048	2.90 lbs (1.310 kg)		Aluminum	N/A	USA Made

Pigeon Mountain Industries, Inc. | PO Box 803, LaFayette, GA 30278 | Fax: 706-764-1531 | Email: custserv@pmirope.com