

Find the right ladder that meets all of your work and rescue specifications.

SKU	Length	Rung Spacing	Rung Finish	Rung Diameter	Rung Width	Rung Material	Side Material	Rung Bending Load	Wire Side Breakage	Rung Slipping Load
<b>COMPACT</b>										
LD39001	5 m	25 cm	Plain	12.5 mm (0.5")	150 mm (5.9")	Aluminum Alloy	4mm, 7x19 Galvanized Steel Cable	2.0 kN (450 lbf)	10.0 kN (2250 lbf)	4.0 kN (900 lbf)
LD39002	5 m	30 cm								
LD39003	10 m	25 cm								
LD39004	10 m	30 cm								
LD39005	5 m	25 cm	Plain, Lightweight	12.5 mm (0.5")	150 mm (5.9")	Aluminum Alloy	3mm, 7x7 Galvanized Steel Cable	2.0 kN (450 lbf)	6.0 kN (1350 lbf)	4.0 kN (900 lbf)
LD39006	5 m	30 cm								
LD39007	10 m	25 cm								
LD39008	10 m	30 cm								
LD39041	5 m	25 cm	Black Anodized	12.5 mm (0.5")	150 mm (5.9")	Black Anodized Aluminum Alloy	4mm, 7x19 316 Stainless Steel Wire Rope	2.0 kN (450 lbf)	10.0 kN (2250 lbf)	4.0 kN (900 lbf)
LD39042	5 m	30 cm								
LD39043	10 m	25 cm								
LD39044	10 m	30 cm								
<b>WIDE RUNG</b>										
LD39045	1 m	25 m	Aluminum	25 mm (1.0")	270 mm (10.6")	Aluminum Alloy	4mm, 7x19 Galvanized Steel Cable	5.0 kN (1125 lbf)	10.0 kN (2250 lbf)	8.0 kN (1800 lbf)
LD39046		30 m								
LD39047	1 m	25 m	Black Aluminum	25 mm (1.0")	270 mm (10.6")	Black Anodized Aluminum Alloy	4mm, 7x19 316 Stainless Steel Wire Rope	5.0 kN (1125 lbf)	10.0 kN (2250 lbf)	8.0 kN (1800 lbf)
LD39048		30 m								
LD39050	1 m	25 m	Wide GRP	34 mm (1.3")	270 mm (10.6")	Fluted Glass, Reinforced Plastic	4mm, 7x19 316 Stainless Steel Wire Rope	5.0 kN (1125 lbf)	10.0 kN (2250 lbf)	5.0 kN (1125 lbf)
LD39051		30 m								
LD39052	1 m	30 m	Wide GRP with Polyester Rope	34 mm (1.3")	270 mm (10.6")	Fluted Glass, Reinforced Plastic	8 mm Polyester Rope	5.0 kN (1125 lbf)	8.0 kN (1800 lbf)	5.0 kN (1125 lbf)

Pigeon Mountain Industries, Inc. | PO Box 803, LaFayette, GA 30278 | Fax: 706-764-1531 | Email: [custserv@pmirope.com](mailto:custserv@pmirope.com)