

Find the right pulley that meets all of your work and rescue specifications.

SKU	Type	Axle	Sheave Size	Tread	HxWxT	Weight	Sheave Material	Side Plate	Max Rope	Breaking Strength	Certifications	
SMC PRUSIK MINDING PULLEYS												
Micro	SM153000N SM153001N	Single	Ball Bearing	1.37"	1.00"	3.75" x 2.55" x 1.12"	3.5 oz (99 g)	Aluminum	Aluminum	1/2" (13 mm)	22 kN (5000 lbf)	NFPA 1983 (2012), T Berry Compliant USA Made
Micro	SM154000N SM154001N	Double	Ball Bearing	1.37"	1.00"	4.65" x 2.55" x 1.81"	5.8 oz (164 g)	Aluminum	Aluminum	1/2" (13 mm)	40 kN (8992 lbf)	NFPA 1983 (2012), T Berry Compliant USA Made
2"	SM152700N SM152701N	Single	Ball Bearing	2.00"	1.50"	2.90" x 3.97" x 1.37"	6.3 oz (179 g)	Aluminum	Aluminum	1/2" (13 mm)	36 kN (8093 lbf)	NFPA 1983 (2012), G Berry Compliant USA Made
2"	SM152800N SM152801N	Double	Ball Bearing	2.00"	1.50"	2.90" x 5.10" x 2.20"	10.4 oz (295 g)	Aluminum	Aluminum	1/2" (13 mm)	46 kN (10341 lbf)	NFPA 1983 (2012), G Berry Compliant USA Made
3"	SM158000N	Single	Ball Bearing	2.97"	2.46"	5.85" x 4.17" x 1.38"	12.5 oz (354 g)	Aluminum	Aluminum	1/2" (13 mm)	38 kN (8542 lbf)	NFPA 1983 (2012), G Berry Compliant USA Made
3"	SM158500N	Double	Ball Bearing	2.97"	2.46"	7.10" x 4.17" x 2.20"	20.0 oz (567 g)	Aluminum	Aluminum	1/2" (13 mm)	48 kN (10790 lbf)	NFPA 1983 (2012), G Berry Compliant USA Made
SMC/RA STAINLESS STEEL PULLEYS												
2"	SM150000	Single	Oilite	2.00"	1.49"	4.60" x 2.50" x 1.40"	8.6 oz (244 g)	Aluminum	Stainless Steel	1/2" (13 mm)	29 kN (6519 lbf)	NFPA 1983 (2012), T Berry Compliant USA Made
2"	SM150500	Single	Ball Bearing	2.00"	1.49"	4.60" x 2.50" x 1.40"	8.6 oz (244 g)	Aluminum	Stainless Steel	1/2" (13 mm)	29 kN (6519 lbf)	NFPA 1983 (2012), T Berry Compliant USA Made
2"	SM155000	Double	Oilite	2.00"	1.49"	6.60" x 2.50" x 2.00"	16.2 oz (460 g)	Aluminum	Stainless Steel	1/2" (13 mm)	41 kN (9217 lbf)	NFPA 1983 (2012), T Berry Compliant USA Made
2"	SM155500N	Double	Ball Bearing	2.00"	1.49"	6.60" x 2.50" x 2.00"	17.0 oz (482 g)	Aluminum	Stainless Steel	1/2" (13 mm)	41 kN (9217 lbf)	NFPA 1983 (2012), T Berry Compliant USA Made
3"	SM151000	Single	Oilite	3.00"	2.34"	6.60" x 3.60" x 1.50"	16 oz (454 g)	Aluminum	Stainless Steel	5/8" (16 mm)	51 kN (11465 lbf)	NFPA 1983 (2012), G Berry Compliant USA Made
4"	SM152000	Single	Oilite	4.00"	3.33"	7.70" x 4.60" x 1.50"	23 oz (652 g)	Aluminum	Stainless Steel	5/8" (16 mm)	51 kN (11465 lbf)	NFPA 1983 (2012), G Berry Compliant USA Made
4"	SM152500	Single	Ball Bearing	4.00"	3.33"	7.70" x 4.60" x 1.50"	23 oz (652 g)	Aluminum	Stainless Steel	5/8" (16 mm)	51 kN (11465 lbf)	NFPA 1983 (2012), G Berry Compliant USA Made
4"	SM157000	Double	Oilite	4.00"	3.33"	9.90" x 4.60" x 2.40"	40.3 oz (1.14 kg)	Aluminum	Stainless Steel	5/8" (16 mm)	63 kN (14163 lbf)	NFPA 1983 (2012), G Berry Compliant USA Made
4"	SM157500N	Double	Ball Bearing	4.00"	3.33"	9.90" x 4.60" x 2.40"	40.3 oz (1.14 kg)	Aluminum	Stainless Steel	5/8" (16 mm)	63 kN (14163 lbf)	NFPA 1983 (2012), G Berry Compliant USA Made

...continued on next page

SKU	Type	Axle	Sheave Size	Tread	HxWxT	Weight	Sheave Material	Side Plate	Max Rope	Breaking Strength	Certifications	
SMC CR & JR PULLEYS												
CR	SM157300 SM157303	Single	Nylon Bushing	1.20"	0.83"	2.70" x 1.75" x 1.07"	1.8 oz (52 g)	Nylon	Aluminum	1/2" (13 mm)	22 kN (5000 lbf)	UIAA 127 EN 12278 Berry Compliant USA Made
JR	SM159300 SM159301	Double	Zinc Coated	1.20"	0.83"	2.84" x 1.75" x 1.56"	3.2 oz (89 g)	Nylon	Aluminum	23/64" (9 mm)	22 kN (5000 lbf)	UIAA 127 EN 12278 Berry Compliant USA Made
JRB	SM159200 SM159201	Double	Zinc Coated	1.20"	0.83"	3.57" x 1.75" x 1.56"	3.3 oz (94 g)	Nylon	Aluminum	23/64" (9 mm)	22 kN (5000 lbf)	UIAA 127 EN 12278 Berry Compliant USA Made
SMC TR PULLEY												
TR		Single	Oilite	1.20"	0.83"	3.00" x 1.75" x 1.07"	2.3 oz (66 g)	Aluminum	Aluminum	1/2" (13 mm)	26 kN (5845 lbf)	Berry Compliant USA Made

SKU	Type	Axle	Sheave Size	Tread	HxWxT	Weight	Sheave Material	Side Plate	Max Rope	Breaking Strength	Certifications	
SMC SWIFTWATER PULLEY												
Swiftwater	SM147000	Single	Ball Bearing	2.00"	1.50"	4.00" x 3.00" x 1.37"	6.0 oz (170 g)	Aluminum	Aluminum	1/2" (13 mm)	34 kN (7786 lbf)	UIAA 127 EN 12278 Berry Compliant USA Made
SMC KOOTENAY HX PULLEY												
Kootenay HX	SM125500	Single	Ball Bearing	3.46"	2.22"	8.67" x 4.34" x 3.40"	26.4 oz (750 g)	Aluminum	Aluminum	5/8" (16 mm)	38 kN (8542 lbf)	NFPA 1983 (2012), G Berry Compliant USA Made

SKU	Type	Axle	Sheave Size	Tread	HxWxT	Weight	Sheave Material	Side Plate	Max Rope	Breaking Strength	Certifications	
SMC SHUTTLE TANDEM PULLEYS												
Cable	SM156303	Tandem	Ball Bearing	1.32"		4.25" x 3.21" x 1.07"	8.0 oz (227 g)	Stainless	Aluminum	1/2" (13 mm)	26 kN (5845 lbf)	Berry Compliant USA Made
Rope	SM156302	Tandem	Ball Bearing	1.32"		4.25" x 3.21" x 1.07"	5.7 oz (162 g)	Aluminum	Aluminum	1/2" (13 mm)	26 kN (5845 lbf)	Berry Compliant USA Made
Xtreme	SM156302	Tandem	Ball Bearing	1.32"		4.25" x 3.21" x 1.22"	7.6 oz (215 g)	Zinc Plated Stainless	Aluminum	1/2" (13 mm)	26 kN (5845 lbf)	Berry Compliant USA Made
SMC ADVANCE TECH HX PULLEY												
Advance Tech HX	SM154900N	Double/Cam	Ball Bearing	1.37"	1.00"	5.08" x 2.74" x 1.97"	9.5 oz (270 g)	Aluminum	Aluminum	1/2" (13 mm)	34 kN (7644 lbf)	NFPA 1983 (2012), T Berry Compliant USA Made

Pigeon Mountain Industries, Inc. | PO Box 803, LaFayette, GA 30278 | Fax: 706-764-1531 | Email: custserv@pmirope.com